

# 2N4856A, 2N4857A, 2N4858A, 2N4859A, 2N4860A, 2N4861A

## N-Channel Silicon Junction Field-Effect Transistor

- Choppers
- Commutators
- Analog Switches

### Absolute maximum ratings at $T_A = 25^\circ\text{C}$

	2N4856A, 2N4857A, 2N4858A	2N4859A, 2N4860A, 2N4861A
Reverse Gate Source Voltage	- 40 V	- 30 V
Reverse Gate Drain Voltage	- 40 V	- 30 V
Continuous Device Dissipation	1.8 W	1.8 W
Continuous Forward Gate Current	50 mA	50 mA
Power Derating	10 mA/°C	10 mA/°C

At 25°C free air temperature:

Static Electrical Characteristics		2N4856A 2N4859A		2N4857A 2N4860A		2N4858A 2N4861A		Process NJ132	
		Min	Max	Min	Max	Min	Max	Unit	Test Conditions
Gate Source Breakdown Voltage 2N4856A, 2N4857A, 2N4858A	$V_{(BR)GSS}$		- 40		- 40		- 40	V	$I_G = -1\ \mu\text{A}$ , $V_{DS} = 0\text{V}$
Gate Source Breakdown Voltage 2N4859A, 2N4860A, 2N4861A	$V_{(BR)GSS}$		- 30		- 30		- 30	V	$I_G = -1\ \mu\text{A}$ , $V_{DS} = 0\text{V}$
Gate Reverse Current 2N4856A, 2N4857A, 2N4858A	$I_{GSS}$		- 250		- 250		- 250	pA	$V_{GS} = -20\text{V}$ , $V_{DS} = 0\text{V}$
			- 500		- 500		- 500	nA	$V_{GS} = -20\text{V}$ , $V_{DS} = 0\text{V}$ , $T_A = 150^\circ\text{C}$
Gate Reverse Current 2N4859A, 2N4860A, 2N4861A	$I_{GSS}$		- 250		- 250		- 250	pA	$V_{GS} = -15\text{V}$ , $V_{DS} = 0\text{V}$
			- 500		- 500		- 500	nA	$V_{GS} = -15\text{V}$ , $V_{DS} = 0\text{V}$ , $T_A = 150^\circ\text{C}$
Gate Source Cutoff Voltage	$V_{GS(OFF)}$	- 4	- 10	- 2	- 6	- 0.8	- 4	V	$V_{DS} = 15\text{V}$ , $I_D = 0.5\ \text{nA}$
Drain Saturation Current (Pulsed)	$I_{DSS}$	50		20	100	8	80	mA	$V_{DS} = 15\text{V}$ , $V_{GS} = 0\text{V}$
Drain Cutoff Current	$I_{D(OFF)}$		250		250		250	pA	$V_{DS} = 15\text{V}$ , $V_{GS} = -10\text{V}$
			500		500		500	nA	$V_{DS} = 15\text{V}$ , $V_{GS} = -10\text{V}$ , $T_A = 150^\circ\text{C}$
Drain Source ON Voltage	$V_{DS(ON)}$		0.75 (20)		0.5 (10)		0.5 (5)	V (mA)	$V_{GS} = 0\text{V}$ , $I_D = ( )$

### Dynamic Electrical Characteristics

Common Source ON Resistance	$r_{ds(on)}$		25		40		60	$\Omega$	$V_{GS} = 0\text{V}$ , $I_D = 0\text{A}$	$f = 1\ \text{kHz}$
Common Source Input Capacitance	$C_{iss}$		10		10		10	pF	$V_{DS} = 0\text{V}$ , $V_{GS} = -10\text{V}$	$f = 1\ \text{MHz}$
Common Source Reverse Transfer Capacitance	$C_{rss}$		4		3.5		3.5	pF	$V_{DS} = 0\text{V}$ , $V_{GS} = -10\text{V}$	$f = 1\ \text{MHz}$

### Switching Characteristics

Turn ON Delay Time	$t_{d(on)}$		5 (20) [-10]		6 (10) [-6]		8 (5) [-4]	ns (mA) [V]	$V_{DD} = 10\text{V}$ , $V_{GS} = 0\text{V}$ $I_{D(ON)} = ( )$ $V_{GS(OFF)} = [ ]$ <b>(2N4856A, 2N4859A)</b> $R_L = 464\ \Omega$ <b>(2N4857A, 2N4860A)</b> $R_L = 953\ \Omega$ <b>(2N4858A, 2N4861A)</b> $R_L = 1910\ \Omega$
Rise Time	$t_r$		3 (20) [-10]		4 (10) [-6]		8 (5) [-4]	ns (mA) [V]	
Turn OFF Delay Time	$t_{d(off)}$		25 (20) [-10]		40 (10) [-6]		80 (5) [-4]	ns (mA) [V]	

### TO-18 Package

See Section G for Outline Dimensions

### Pin Configuration

1 Source, 2 Drain, 3 Gate & Case

### Surface Mount

SMP4856A, SMP4857A, SMP4858A,  
SMP4859A, SMP4860A, SMP4861A



1000 N. Shiloh Road, Garland, TX 75042  
(972) 487-1287 FAX (972) 276-3375

[www.interfet.com](http://www.interfet.com)